

Elite

Secure Ultra

deposition aid/drift retardant for pesticide sprays



Control the Impact

- Dependable polyacrylamide technology puts the active ingredient application where you want it and keeps it there.
- Manages droplet formation within the optimum VMD to limit rebound bounce and run-off.
- Compatible with most pesticides and spraying equipment.
- Effective drift control at very low use rates.

Directions for Use

Follow the recommendations of the most restrictive active ingredient label.

Tank mixtures should only be applied within the label recommendations of every product in the tank mixture.

Use Rates

Spray Pressure	Nozzle Orientation	Use Rate
Aerial applied below 45 psi	Straight Back	2 - 6 ounces/100 gal
	45° Angle Back	4 - 8 ounces/100 gal
GROUND APPLICATION		
Low (below 30 psi)	Flat Fan, Flooding	1 - 4 ounces/100 gal
	Off-Center	3 - 5 ounces/100 gal
Medium (30 - 50 psi)	Flat Fan, Flooding	3 - 4 ounces/100 gal
	Off-Center	4 - 6 ounces/100 gal
Spray Guns	Low pressure (over 50 psi)	5 - 8 ounces/100 gal
	High pressure (over 50 psi)	8 - 32 ounces/100 gal



Red River Specialties

1324 N. Hearne Ave., Ste 120

Shreveport, LA 71107

T 1 800 256 3344

318 425 5944

F 318 227 3032

visit azelisamericas.com | rrsi.com

creating value,
growing together